


■ greenius®
Lite Line

LED-TRIPROOF



LED-TRIPROOF *Lite Line*



Highly efficient LED triproof (moisture-proof luminaire) for use in extreme operating environments: bright, robust (IK10) and jet-proof (IP 66). Impact-resistant, shatterproof cover made of PC (polycarbonate) in accordance with the requirements of the International Featured Standard Food (IFS Food).

PRODUCT DATA

Power (adjustable)	40 W 45 W 55 W 60 W
Product dimensions	150 cm x 8.5 cm x 7 cm
Luminous flux	5,600 Lumen - 8,400 Lumen
Efficiency	≤140 Lumen / Watt
Beam angle	120°
LED Chip Brand type	Epistar SMD2835
Number of LEDs	252 pcs.
LED Driver Brand Type	Tridonic LC 71W 250-350mA flexC Ip ADV
Material: housing cover	Aluminium PC (Polycarbonate) PC (Polycarbonate)
Colour Rendering Index (CRI)	> 80 Ra
Useful life Failure rate	> 50,000 hrs. L80B10
IP- and IK-Classification	IP66 IK10
Options	Incl. 2. connector and mounting clips 3-phase through-wired
Ambient temperature (ta)	-30 °C to +60 °C
Correlated Colour Temperature (CCT)	neutral white: 4K daylight: 5K daylight+: 6K
Deviation of the colour adjustment	SDCM <5
Certification (LED / Driver)	CE (LVD) CE (EMC) Rohs (2011/65/EC) D-Mark ENEC
Voltage	100 - 240 VAC 50/60 Hz
Item number	TP150-LL

LOGISTICS DATA

Product weight	2.2 kg
Packaging unit	6 pcs.
Weight packing unit	17 kg
Dimensions packing unit	163 cm x 28 cm x 18 cm